



Material Safety Data Sheet (MSDS)

Canon 6035 Toner

Document #1009-003-01
REV:1/2015

PRODUCT IDENTIFICATION

Product Name: Canon 6035 Toner P-205G1

COMPONENTS

INGREDIENT	Cas No.	WT%	OSHA (PEL)	ACGIH (TLV)
Thermoplastic Resin	2576-47-9	40-50	NA	NA
Iron Oxide	1317-61-9	40-50	NA	NA
Organic Dye	101357-15-7	0-5	NA	NA
Wax	9003-07-0	1-5	NA	NA

PHYSICAL DATA

Approx. Boiling Point N/A	Vapor Density (air=1) N/A	Vapor Pressure N/A	Evaporation Rate (n-BuAC=1) N/A	% Volatile N/A
Specific Gravity appx 1.5	Flash Point Range N/A	Melting Point NA	Solubility in Water Insoluble	Appearance/Odor Odorless, black fine powder

EMERGENCY FIRST AID

For Emergency Information Call 047-433-9181.

Eye Contact: Flush with copious amounts of water for at least 15 minutes, consult a physician if irritation persists.

Skin Contact: Wash with mild soap and water. If irritation persists, seek medical attention.

Inhalation: Move subject to fresh air.

Ingestion: If swallowed, give 2 glasses of water to drink and consult a physician. Never give anything by mouth to an unconscious person.

HEALTH HAZARDS/ROUTES OF ENTRY

Eye Contact: Heavy dusting can cause slight irritation.

Skin Contact: Prolonged or repeated skin contact can cause slight irritation

Inhalation: Inhalation of toner vapor from heated product can cause headache, nausea, irritation of the nose, throat and lungs.

Ingestion: N/A.

SPECIAL PROTECTION INFORMATION

Ventilation: Local ventilation during bulk handling. General ventilation during mechanical operation.

Respiratory Protection: Dust mask during bulk handling.

Protective Gloves: Protective gloves are recommended.

Eye Protection: Eye protection is recommended.

Other Protection: It is suggested that a source of clean water be available in work area for flushing eyes. Avoid inhalation of dust.

REACTIVITY DATA

Stability	Incompatibility (Materials to Avoid)	Hazardous Decomposition Products	Hazardous Polymerization
Stable Avoid temperatures above 150°C	This product is not compatible with strong oxidizers.	N/A.	Will not occur.

SPILL OR LEAK PROCEDURE

Floors may become slippery, use care to avoid falling. Transfer spilled material to suitable containers for recovery or disposal. Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

PRECAUTIONS IN CASE OF SPILL

Floors may become slippery, use care to avoid falling. Transfer spilled material to suitable containers for recovery or disposal. Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHOD

Dispose of product in accordance with local, county, state and federal regulations.

HANDLING AND STORAGE PRECAUTIONS

The maximum recommended storage temperature for this material is 50°C. Monomer vapors can be evolved when material is heated during processing operations. See personal protection information for more cautions.

FIRE AND EXPLOSION INFORMATION - HAZARD RANKING

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

TOXICITY: 1 **FLAMMABILITY: 2** **REACTIVITY: 0** **OTHER: N/A**

Extinguishing Media: Dry chemicals, CO2 or foam.

Hazardous Decomposition: N/A

Fire Fighting Procedures: Material as solid is combustible; burns vigorously with intense heat.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

This information in this document is believed to be correct as of the date issued. However, no warranty of Merchantability, fitness for any particular purpose, or any other warranty is expressed or is implied regarding the accuracy or completeness of this information, the results to be obtained from use of this information or the product, the safety of this product, or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.